


	ES-120LS3-550	
System Performance	Metric	British
Rated Random/Sine Force	120 kN	26000 lbf
Rated Shock Force	240/360* kN	54000/80000* lbf
Usable Frequency	2-2500 Hz	
Maximum Velocity	2/2.5* m/s	78.7/98.4* in/s
Maximum Acceleration	1000 m/s ²	100 g
Maximum Payload	1000 kg	2205 lbs
Maximum Displacement p-p	76 mm	3 in
Resonance Frequency		
Shaker Model	ET-120LS3	
Mass of Moving Elements	90 kg	198 lbs
Armature Diameter	550 mm	21.7 in
Weight	About 7300 kg	About 16093 lbs
Body Suspension Natural Frequency	2.5 Hz	2.5 Hz
Dimension L×W×H	1930×1280×1363 mm	76×50.4×53.7 in
Power Amplifier Model	DA-120	
Power	120 kVA	
Power Supply Requirement	180kVA	
Weight	About 1900 kg	About 4189 lbs
Dimension L×W×H	1770×850×1983 mm	69.7×33.5×78 in
Cooling Type	Water Cooling	
Cooling Unit Model	CU-2	
Internal Circle Water Flow (Distilled Water)	80 L/min	17.6 gal/min
Internal Circle Water Pressure (Distilled Water)	1 Mpa	145 psi
External Circle Water Flow (City Water)	160 L/min	35.2 gal/min
External Circle Water	0.25~0.4 Mpa	36-58 psi

Pressure (City Water)		
Water Pump Power (Internal/External)kW	8/4 kW	
Distilled Water Requirement	Hardness 30ppm, PH7~8, Conductivity 1Us/cm	
Unit Weight (kg)	About 300 kg	About 661 lbs
Dimension L×W×H	610×850×1983 mm	24×33.5×78 in



NOTE: In keeping with our commitment to continuous product improvement, the information herein is subject to change.
Copyright 2012 Dongling Vibration Test Instrument Co., Ltd. All rights reserved.